

# 112022

**Drums 2SW VL18-125-6000 1-1/4"**






| | |
|---|---|
| **Unit** | Pair |
| **Box** | 4 |
| **Pallet** | 64 |
| **Weight (kg)** | 3.8 |

## Product description

Is used for Vertical lift doors. Supplied with 2 set screws forfixation on shaft. One cable set screw for cable fixation. Formore information ask for a customer drawing. Minimum walloffset = 152mm. Max torque bolts 15Nm. Material: Aluminium Max. door height: 6000 mm.
Max. door weight: VL<4000 mm = 600 kg / VL>4000 mm = 500 kg Max. cable diameter: 5mm. Shaft diameter: 1,25 inch (31,75 mm). Marking: Red = Left, Black = Right.

## Technical information

| | |
|---|---|
| **Industrial** | |
| **System** | Vertical lift |
| **Max. load (kg)** | 500-600 |
| **Shaft diameter ("/mm)** | 1.25" (31,7) |
| **Safety windings** | 2.0 |
| **Material** | Die-cast Aluminium |
| **Cable diameter (mm)** | 5 |
| **Max. height 0.5 safety (mm)** | - |
| **Max. height 2.0 safety (mm)** | 6000 |
| **Offset (mm)** | 152 |

This information is subject to change. Check our website for updates. This document was generated on 2026-11-03 07:02 GMT...